

## C47\_Stopwatch

Label	Key location	Description
<b>R/S</b>	primary R/S (C47.84.11)	Start/stop stopwatch
<b>ADD</b>	<i>Menu STOPW Page 1 primary F1</i>	<i>Add timestamp to statistics matrix (STATS)</i>
<b>0.1s</b>	<i>Menu STOPW Page 1 primary F4</i>	<i>Show running time with tenths of seconds</i>
<b>RESET</b>	<i>Menu STOPW Page 1 primary F6</i>	<i>Reset the stopwatch</i>
↵	primary ↵ (C47.45.11)	Reset the stopwatch
[0][0]	primary [0] (C47.82.11)	Set Current Register Address (CRA) for stopwatch (lower/upper bound)
[9][9]	primary [9] (C47.54.11)	
<b>ENTER</b>	primary ENTER (C47.41.11)	Store timestamp in Current Register Address and increase CRA
[▲]	primary [▲] (C47.51.11)	Increase Current Register Address (CRA)
[▼]	primary [▼] (C47.61.11)	Decrease Current Register Address (CRA)
<b>STOPW</b>	gShifted [0] (C47.82.13)	While in the app, open the Current Register Address for input (00..99)
[.]	primary [.] (C47.83.11)	Combines ENTER and ↵
[+]	primary [+] (C47.85.11)	Combines ENTER and ADD
<b>RCL</b>	primary RCL (C47.32.11)	Recall and add register value to running timer
<b>SNAP</b>	gShifted EXIT (C47.81.13)	Save screenshot as image to bitmap file in FLASH memory
<b>EXIT</b>	primary EXIT (C47.81.11)	Exit stopwatch